

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 September 2001 (20.09.2001)

PCT

(10) International Publication Number
WO 01/68227 A1

(51) International Patent Classification⁷: **B01D 61/10**

[US/US]; 7907 Thornapple Drive, Russell, OH 44072 (US); **ELLIS, George, III** [US/US]; 14820 Stillwell Road, East Claridon, OH 44033 (US).

(21) International Application Number: PCT/US00/06848

(22) International Filing Date: 15 March 2000 (15.03.2000)

(74) Agent: **HLAVKA, John, R.**; Watts, Hoffmann, Fisher & Heinke Co., L.P.A., P.O. Box 99839, Cleveland, OH 44199-0839 (US).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): CA, US.

(71) Applicant (*for all designated States except US*): **KLNETICO INCORPORATED** [US/US]; 10845 Kinsman Road, Newbury, OH 44065 (US).


Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HALEMBA, Peter**

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLUID TREATMENT SYSTEM



(57) Abstract: A water treatment system having a reverse osmosis unit (14) includes a storage tank (40) having an outer tank housing (42) that encloses an expandable bladder (50). A pressurized region (62) is defined between the outside of the bladder (50) and inside of the housing (42). A control valve assembly (44) controls communication of source water under pressure to pressurizing region (62) and communicates the region (62) with a drain (22). The assembly (44) includes a pilot valve (70) that is responsive to a state of dispensing and includes a valve element (76) that moves between a first dispensing position and a second non-dispensing position. A servo valve (72) is responsive to position of the pilot valve (70) and communicates source water under pressure to the region (62) when the pilot valve (70) is in the first position thus applying pressure to bladder (50) to expel treated water and communicates region (62) to the drain (22) when dispensing is not occurring so as to allow bladder (50) to expand as it receives treated water from the reverse osmosis unit (14).

WO 01/68227 A1